

**Product Data Sheet****PRODUCT DESCRIPTION**

7031-100 Water-Borne Acrylic primer is a single component primer designed to seal and prepare surfaces for NEOFLEX Coatings where a solvent-borne system is not appropriate. 7031-100 is the perfect choice to prime and seal acrylic-based mortar systems generally associated with Exterior Insulated and Finish Systems.

**PRODUCT NUMBER AND COLOR**

Standard Color: 7031-100 White

**CURED RESIN PERFORMANCE**

Description	Test Method	Results
Water Resistance	ASTM D471	<20%
Adhesion	ASTM D903	5 lb/in
MVT @ 3 Mils	ASTM E96	30 English

The above tested results are typical values. Individual lots may vary up to 10% from the typical value.

**PRODUCT DATA**

Description	Test Method	Results
Weight/Gal	ASTM D1475	9.5 lbs/gal
Weight Solids	ASTM D5201	34%
Volume Solids	ASTM D5201	24%
VOC	ASTM D5201	96.66 g/L
Viscosity	ASTM D562	82 KU
Flash Point	ASTM D3278	None
Dry Time (8 wet mils)	ASTM D5895	1 hour @ 75°F, 50% RH

The above tested results are typical values. Individual lots may vary up to 10% from the typical value.

**APPLICATION**

Surfaces should be clean, dry and structurally sound.

Apply at a rate of 200 - 400 square feet per gallon depending upon surface and condition. May be brushed, rolled or sprayed. **DO NOT APPLY WHEN TEMPERATURE IS BELOW 45 °F.**

**HEALTH AND SAFETY**

Read the Material Safety Data Sheet (MSDS) and container labels for detailed health and safety information. This product is intended for industrial use by properly trained professional applicators only.

**STORAGE**

Cans of primer material should be stored in a cool (75°F) area.

**AVOID FREEZING**

The information, data and suggestions contained herein are believed to be reliable, based upon our knowledge and experience; however, it is expressly declared that Seller does not guarantee the result to be obtained in Buyer's process. **SELLER HEREBY EXPRESSLY DISCLAIMS ANY IMPLIED WARRANTY OF MERCHANTABILITY FOR FITNESS FOR A PARTICULAR PURPOSE AND/OR ANY OTHER WARRANTY, EXPRESS OR IMPLIED** as to any and all products and/or suggestions described herein, whether such products are used alone or in combination with other materials. Buyer must make its own determination of the suitability of any product for its use, and the completeness of any information contained herein. Nothing contained herein shall be construed to constitute inducement or recommendation to practice any invention covered by any patent without authority from the owner of the patent. Applicator is an independent contractor of, and should under no circumstances be viewed as an employee or agent of, the NEOGARD® Division of JONES-BLAIR®. 02262010/7031-100PD.indd

**NEOGARD®**

Div. of JONES-BLAIR®

2728 Empire Central - Dallas, Texas 75235 - Toll Free (800) 321-6588 - Fax (214) 357-7532 - www.neogard.com